



Search by: Keyword Product



[Home](#) [Products/Parts](#) [Register Product](#) [Locate Distributor](#) [Contact Us](#) [Press/Media](#) [Distributor Login](#) [Site Map](#)

Overview & Specifications

Advanced Specifications

Manual/Guides [➤](#)

Diagrams/Drawings [➤](#)

Parts/Kits [➤](#)

Bulletins [➤](#)

[Product/Parts](#) > [Gasoline Generators](#) > [3.0 BPMG - 60 Hz](#) > Overview & Specifications

3.0 BPMG - 60 Hz - Overview & Specifications

Cylinders: 2
Bore: 2.32 in.
Stroke: 2.36 in.
Displacement: 20.00 cu. in.
Aspiration: Natural

Length: 24.57 in.
Width: 13.59 in.
Height: 14.48 in.
Weight: 165.00 lbs.



Also available at 50 Hertz - Still 3.0 kW!

The Most Compact 3.0kW

The 3.0 BPMG not only has the smallest envelope available for a 3.0 kW, there is not another generator like it. The 3.0 BPMG was specifically designed for the small boat owner who previously didn't have available space to accommodate a generator with "punch."

Lightweight & Powerful

Weighing in at only 165 pounds, the 3.0 BPMG is powerful enough to run an air conditioner or water heater, etc.

Smooth & Quiet Operation

Operating with 2-cylinders instead of 1, at a low 2200-rpm instead of 3600, and with a specially designed flywheel: the 3.0 BPMG provides smooth performance and doesn't require a sound shield.

Simple Installation

The 3.0 BPMG is a simple "plug & play" genset with minimal wiring in the control box. An optional remote start/stop is available with harness to plug into the side of the control box.

Easy Operation

A simple "one-touch" rocker switch eliminates the need for separate start, stop and priming switch.

Clean Exhaust

The 3.0 BPMG incorporates a catalytic converter and meets all EPA and CARB requirements.

Electronic Governor

Maintains steady speed, provides optimum fuel efficiency and eliminates "bogging down" when load is applied.

Permanent Magnet Generator

A small, compact and completely sealed permanent magnet generator provides 5% voltage regulation, no-load to full-load, and produces a "utility grade" sine wave.

Standard Equipment

- Simple, "one touch" start/stop control panel with running hour meter
- Overspeed Protection
- Battery Charger
- Belt-driven, raw water pump
- Lube oil drain hose
- Operator's manual and parts list
- Electronic Governing
- Safety shut-downs - overspeed, low oil pressure, high exhaust temperature
- A.C circuit breaker
- Water injected exhaust elbow
- Vibration mounts
- Belt guards
- EPA, CARB & CE compliant
- Meets U.S.C.G. regulation 33CFR-183

Optional Equipment

- Remote start/stop panel
- Hydro-hush muffler and fittings
- Anti-siphon valve for overboard cooling water discharge
- Ship-shore switch
- "A" on-board spare parts kit; "B" extended cruising spare parts kit
- Technical manual



[Download Catalog](#)

Westerbeke Corp., Myles Standish Industrial Park
 150 John Hancock Rd., Taunton, MA 02780-7319 USA

Please Note: While every attempt is made to ensure the information on this site is accurate, this data is provided for information purposes only and is subject to change without notice.

©2009 All Rights Reserved by Westerbeke Corp. Site development by iiCREATIVE Programming by The Computer Company, Inc.
 Westerbeke marine products included in this website: Westerbeke marine generators, Westerbeke gasoline generators, Westerbeke diesel generators, Westerbeke industrial generators, Westerbeke D-Net™ generators, Westerbeke marine engines, Westerbeke sound guards™, Westerbeke Safe-CO® gasoline generators, Westerbeke Rotary Aire marine climate control, and Universal marine engines by Westerbeke.