



Search by: Keyword Product



[Home](#) [Products/Parts](#) [Register Product](#) [Locate Distributor](#) [Contact Us](#) [Press/Media](#)

Overview & Specifications

Advanced Specifications

Manual/Guides [➤](#)

Diagrams/Drawings [➤](#)

Parts/Kits [➤](#)

Bulletins [➤](#)



Download Catalog

[Product/Parts](#) > [D-NET Diesel Generator](#) > [5.5 EDC D-NET](#) > Overview & Specifications

5.5 EDC D-NET - Overview & Specifications

Cylinders: 3

Bore: 2.99 in.

Stroke: 2.76 in.

Displacement: 58.09 cu. in.

Aspiration: Natural

Length: 27.80 in.

Width: 18.50 in.

Height: 20.60 in.

Weight: 373.00 lbs.

Sound Guard Enclosure

The First Electronic Diesel Generators Available NMEA 2000® Certified

The wave of the future, Westerbeke D-NET™ electronic generators are offered with NMEA 2000® compliant databus communication. NMEA 2000® is a network for shipboard National Marine Electronics Association (NMEA) standards. NMEA 2000® generator components, allow boat builders and their customers to significantly reduce the run cables throughout the vessel. All certified components freely communicate using "T" connections that simplify networking.

Information At Your Fingertips

All Westerbeke D-NET™ generators have available digital controls offering simple operational status and, if necessary, system diagnostics. Westerbeke also features proper operation. They monitor battery voltage, generator voltage, generator temperature. All this information may be viewed from a distance—all green light properly. Further details are available on the screen display. The user may control information without encountering "codes". Westerbeke uses text so the user does not see numeric information.

Quiet, Slow-Speed, Digital Operation

Operating at 1800 RPM with newly designed, tuned air intake silencer and 3-cylinder smooth and quiet. Augmenting this desired effect is the electronic governing that is applied. Include the optional Sound Guard SST with high quality stainless steel aluminum panels and you have a generator as attractive as it is quiet.

Standard Features

- Digital display and diagnostics panel
- Electronic governing
- Tuned air intake silencer
- Anti-vibration mounts
- Lube oil drain hose

- Safety shut-downs: overspeed, underspeed, low oil pressure, high exhaust and high coolant temperature
- A.C. circuit breaker
- 50 amp battery charging alternator
- Power take-off interface
- Self-bleeding fuel system
- Fresh water cooling and coolant recovery tank
- 45 degree water injected exhaust elbow
- Gear driven raw water pump
- Oil fill - top and side
- Belt guard
- Operator's manual
- 5-year limited warranty
- EPA, CARB & CE compliant

Optional Equipment

- NMEA 2000® compliant databus communication
- Remote start-stop panel
- Remote panel extension cables
- Ship shore switch
- Power takeoff adapter
- Fuel filter/water separator
- Hydro hush muffler and fittings
- "A" on-board spare parts kit
- "B" extended cruise control
- Anti-siphon valve for discharge water
- Technical Manual
- Sound Guard SST

Optional 5.5 EDC Sound Guard SST

The optional [Sound Guard SST](#) enclosure provides optimum silencing for the generator steel frame and powder coated aluminum panels; the Sound Guard SST also provides panels removable for easy servicing and maintenance.

© 2009 All Rights Reserved by Westerbeke Industrial Generators, Inc. Site development by CREATIVE PROGRAMMING, Inc. This document is provided for information purposes only and is not intended to constitute an offer. Westerbeke marine products included in this website: Westerbeke marine generators, Westerbeke gasoline generators, Westerbeke industrial generators, Westerbeke D-Net™ generators, Westerbeke marine engines, Westerbeke sound guard SST, Westerbeke Safe-CO® gasoline generators, Westerbeke Rotary Aire marine climate control, and Universal marine engine.