




Search by: Keyword Product






[Home](#)
[Products/Parts](#)
[Register Product](#)
[Locate Distributor](#)
[Contact Us](#)
[Press/Media](#)
[Distributor Login](#)
[Site Map](#)


Overview & Specifications

Advanced Specifications

Manual/Guides 

Diagrams/Drawings 

Parts/Kits 


Bulletins 

[Product/Parts](#) > [Gasoline Generators](#) > [7.0 BCGD Low-Profile](#) > Overview & Specifications

7.0 BCGD Low-Profile - Overview & Specifications

Cylinders: 3
Bore: 2.56 in.
Stroke: 2.61 in.
Displacement: 40.30 cu. in.
Aspiration: Natural

Length: 26.18 in.
Width: 15.48 in.
Height: 16.85 in.
Weight: 336.00 lbs.



The Most Compact 7.0 kW Available

Due to its unique design, the 7.0 BCGD gasoline generator has the smallest envelope available with slow speed operation.

Quiet

The 7.0 BCGD operates at a quiet 1800 RPM. So quiet, it does not require a sound enclosure.

Smooth Operation

Operating with 3-cylinders and a balance shaft that virtually eliminates vibration, the 7.0 BCGD is an extremely smooth running generator set.

Durable and Reliable

The 7.0 BCGD runs at 28% of its maximum engine speed, so the owner can expect more durability and reliability.

Easy Maintenance

To minimize engine maintenance, the 7.0 BCGD is fresh water cooled and equipped with a simple control system. Easy access to all servicing points (single side servicing) allows easy installation and routine maintenance.

Five Year Limited Warranty

The 7.0 BCGD is backed by Westerbeke's 5-year limited warranty. The presence of Westerbeke in over 65 countries around the world provides customers with easy access to parts, service and technical support worldwide. Established in 1937, Westerbeke is committed to providing its customers with quality products and unequalled after sales support.

Standard Equipment

- Fresh water cooling
- Vibration mounts
- 90° water injected exhaust elbow
- Coolant recovery tank
- 17 amp battery charger
- Simple start/stop control panel with running hour meter
- Belt guard
- Belt-driven, raw water pump
- Electronic governing
- Generator field adjustable to 50 or 60 Hz
- Lube oil drain hose
- Safety shut-downs – hi-coolant temperature, low oil pressure, hi-exhaust temperature
- A.C. Circuit Breaker
- Operator's manual and parts list
- EPA, CARB & CE compliant
- Meets U.S.C.G. Regulation 33CFR-183
- Overspeed protection

Optional Equipment

- Remote start/stop panel
- Ship-shore switch
- Hydro-hush muffler and fittings
- "A" on board spare parts kit
- "B" extended cruising spare parts kit
- Anti-siphon valve for overboard cooling water discharge
- Technical Manual



Westerbeke Corp., Myles Standish Industrial Park
 150 John Hancock Rd., Taunton, MA 02780-7319 USA

Please Note: While every attempt is made to ensure the information on this site is accurate, this data is provided for information purposes only and is subject to change without notice.

©2009 All Rights Reserved by Westerbeke Corp. Site development by iCREATIVE Programming by The Computer Company, Inc.
 Westerbeke marine products included in this website: Westerbeke marine generators, Westerbeke gasoline generators, Westerbeke diesel generators, Westerbeke industrial generators, Westerbeke D-Net™ generators, Westerbeke marine engines, Westerbeke sound guards™, Westerbeke Safe-CO® gasoline generators, Westerbeke Rotary Aire marine climate control, and Universal marine engines by Westerbeke.